Ser. No.: 10/774,123 Peter W. Swart, <u>et al.</u>

Page 2 of 8

Specification Amendments:

Please amend paragraph 24 of the specification as follows:

--[0024] The present invention provides an air bath 10. Figures 1-7 illustrate the configuration of its basin 12 as well as the arrangement of air jets 14. Figure 8 illustrates schematically the air delivery system that can be used with the basin of FIGS. 1-7 as well as the basin 12' shown in FIG. 8. The difference between the two basins is that the basin 12' is specially configured, as will be described, to provide selective control of air flow to prescribed zones, for example, head, lumbar, and foot zones. Figure 8 also illustrates that the air bath can include a chromatherapy system 18 to illuminate the bath water various colors. A suitable chromatherapy system is disclosed in U.S. patent patents 6,360,380 and application Ser. No. 10/068,395, filed February 6, 2002 6,752,517, both assigned to the assignee of the present invention and hereby incorporated by reference as though fully set forth herein. Also, in any case, the tub basin can be configured as a conventional bathtub, whirlpool, spa or swimming pool.--

Please amend paragraph 28 of the specification as follows:

--[0028] All three of the rows 40A-40C are near the bottom 20 and preferably do not extend into the upper half of the side walls. More preferably, each row is spaced apart vertically about 5/8 inch, and no less than about 1/2 inch. Much less than about 1/2 inch vertical spacing has been determined to be too small to achieve the desired benefits discussed below. The upper range of the spacing is limited by other factors, such as the height of the side walls, the intended water depth in the basin, whether a single manifold will be used, and if so the ability to achieve sufficient force through the jets without too stringent of air flow requirements.--